



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Titanium powder filter cartridge

Filter media: Titanium powder

Seal ring material: Silicone, Viton, EPDM, PTFE

Max. working temperature: $\leq 200^{\circ}\text{C}$

Max. working pressure drop: 300Mpa/23 $^{\circ}\text{C}$

Rating: 1, 2, 5, 10, 20, 50, 75, 100 micron

Length: 210, 250, 350, 500, 750, 1000mm

OD: 20, 30, 50, 60, 70, 90mm

Connector: M20 M30 M32 222 226

Product Description:

Yitong titanium filter cartridge is based on pure titanium powder (Purity 99.7% or higher) as the main raw material. After high heating sintering, it appears uniform structure and high density pores. It also has great filtration precision and high flow rate. It can be used for solid liquid, gas separation and purification. The perfect strength and titanium media makes it is able to withstand harsh high temperature and pressure working environments.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Performance Feature:

- 1 High flow rate
- 2 Easily to be cleaned, long service life
- 3 High filtration rating
- 4 High temperature and high pressure resistance
- 5 Good strength

Application:

- 1 seawater desalination and sewage treatment
- 2 Filtration of the acid, alkali, strong oxidizing and strong polarization liquid
- 3 Filtration of the oil and organic solvents.
- 4 Decarburization filtration
- 5 The end filtration of the mineral water and purified water.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Technical Parameter:

Cartridge structure	Filter media	Titanium powder
	Seal ring material	Silicone,Viton,EPDM,PTFE
Working situation	Max.working temperature	≤200℃
	Max. working pressure drop	300Mpa/23℃
Rating	1, 2, 5, 10, 20, 50, 75, 100 micron	
Length	125, 250, 350, 500, 750, 1000 mm	
OD	20, 30, 50, 60, 70, 90mm	
Connector	M20 M30 M32 222 226	

Packing and shipping:



Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications,such as the material,length,micron,adapter,apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q:How longabout your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail:manager@yitong-filter.com

WhatsApp:+86 180 3376 5689

WeChat: +86 180 3376 5689